Pharmacy Plus Bluetooth

Enabled Refrigerator

158L Pharmacy Plus Undercounter Fridge with Glass Door – Integrated Drawers

Product code PPGR158BT-DWP

SKU code 444411388









Key features

- √ Temperature range of +2°C to +8°C
- √ Audible and visual temperature alarms
- √ Solid and glass door options
- ✓ Integrated lock, supplied with 2 keys for added security



4.3









Bluetooth Connected Controller

Our controller is Bluetooth enabled and allows for simple, contactless monitoring of temperature and alarm history, via the official Lec Medical app. Battery back-up, provides continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Integrated Drawers

These slide out drawers include dividers to assist with stock rotation and keep contents organised



SKU Code	444411388
Product Code	PPGR158BT-DWP
Gross Capacity (litres)	158L
Net Capacity (litres)	145L
Unit External Width (mm)	595mm
Unit External Depth (mm)	600mm
Unit External Height (mm) Product Weight (kg)	850mm 45.56kg
Packed Width (mm)	43.36kg 640mm
Packed Width (mm)	660mm
Packed Height (mm)	910mm
Packed Weight (kg)	50.57kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	495mm x 480mm x 720mm
Temperature Range	+2°C to +8°C
Colour External Finish	White/green
Internal Finish	Painted Steel HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	PVC / Glass
Door Type	Glass
Door Style	Hinged, Reversible
Door Liner	Glass
Number of Door Trays	N/A
Number of Door Tray Positions	N/A
Door Open Depth (mm)	1150mm
Replacement Door Seal Open Door Sensor	Yes Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	4 All adjustable
Porthole	Yes
Porthole Size	16mm
Porthole Location	Rear Bottom (Right)
Temperature Display on Panel	Yes
Temperature Alarm Remote Alarm Contacts	Yes Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	4
Number of Shelf Positions	3 Fixed
Shelf Size (mm) (WxDxH)	N/A
Shelf Size 2 (mm) (WxDxH)	N/A
Shelf Material	N/A
Drawer Size (mm) (WxDxH) Drawer Size 2 (mm) (WxDxH)	419mm x 374mm x 60mm N/A
Drawer Material	ABS
Number of Baskets	1
Basket Material	Polythene Coated Wire
Basket Size (mm) (WxDxH)	485mm x 255mm x 171mm
Interior Light	Yes
Light Type Light Activation	LED Door Switch / App
Fan	Door Switch / App Yes - Tangential
Spark Free	No
Defrost setting	Auto (Off Cycle)
Controller Type	Digital BT, External
Battery Back Up/Hours	Yes/48hrs
Bluetooth	Yes
Number of Probes	2
Probe Type Ambient Temperature Range	Air & Load (Silicone Oil) 10°C to 32°C
Refrigerant Type	R600a/28g
UK 3 Pin Plug	Yes
Other Plug Types Available	No
Voltage Supply	220-240V
Frequency (Hz)	50Hz
Max Power (W)	101W
Max Current Rating (A)	0.78A
Energy Consumption (kWh/24h) Energy Consumption AE (kWh)	0.92kWh/24h 328.5kWh
Noise Level (dB)	40.1dB
Insulation Thickness (mm)	45mm
Insulation Type	High Density Polyurethane Foam
Blowing Agent	Cyclopentane
Anti-Microbial Handle	Yes

