

Pharmacy Plus Bluetooth Enabled Refrigerator

310L Pharmacy Plus Upright Fridge with Solid Door

Product code PPSR310BT

SKU code 444411313



Key features

- ✓ Temperature range of +2°C to +8°C
- ✓ Audible and visual temperature alarms
- ✓ Solid and glass door options
- ✓ Integrated lock, supplied with 2 keys for added security



Bluetooth Connected Controller

Our controller is Bluetooth enabled and allows for simple, contactless monitoring of temperature and alarm history, via the official Lec Medical app. Battery back-up, provides continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aids in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.

| | |
|-------------------------------------|--------------------------------|
| SKU Code | 444411313 |
| Product Code | PPSR310BT |
| Gross Capacity (litres) | 310L |
| Net Capacity (litres) | 305L |
| Unit External Width (mm) | 595mm |
| Unit External Depth (mm) | 600mm |
| Unit External Height (mm) | 1560mm |
| Product Weight (kg) | 51.41kg |
| Packed Width (mm) | 640mm |
| Packed Depth (mm) | 635mm |
| Packed Height (mm) | 1630mm |
| Packed Weight (kg) | 57.21kg |
| Country of Origin | UK |
| Internal Dimensions (mm) (WxDxH) | 500mm x 480mm x 1445mm |
| Temperature Range | +2°C to +8°C |
| Colour | White/green |
| External Finish | Painted Steel |
| Internal Finish | HIPS* |
| Type of plastic | SRL800 (HIPS/ABS mix) |
| Door Finish | Painted Steel / HIPS* |
| Door Type | Solid |
| Door Style | Hinged, Reversible |
| Door Liner | Flat |
| Number of Door Trays | N/A |
| Number of Door Tray Positions | N/A |
| Door Open Depth (mm) | 1150mm |
| Replacement Door Seal | Yes |
| Open Door Sensor | Yes |
| Lock | Yes, 2 Keys |
| Adjustable Feet (number & position) | 2 Adjustable (front) |
| Porthole | Yes |
| Porthole Size | 16mm |
| Porthole Location | Rear Bottom (Right) |
| Temperature Display on Panel | Yes |
| Temperature Alarm | Yes |
| Remote Alarm Contacts | Yes |
| Audible Alarms | Yes |
| Visual Alarms | Yes |
| Number of Shelves/Drawers | 5 |
| Number of Shelf Positions | 9 |
| Shelf Size (mm) (WxDxH) | 496mm x 405mm x 6mm |
| Shelf Size 2 (mm) (WxDxH) | 493mm x 265mm x 6mm |
| Shelf Material | White Polythene Coated Wire |
| Drawer Size (mm) (WxDxH) | 2@ 408mm x 405mm x 195mm |
| Drawer Size 2 (mm) (WxDxH) | N/A |
| Drawer Material | N/A |
| Number of Baskets | 1 |
| Basket Material | White Polythene Coated Wire |
| Basket Size (mm) (WxDxH) | 485mm x 255mm x 171mm |
| Interior Light | Yes |
| Light Type | LED |
| Light Activation | Door Switch / Controller |
| Fan | Yes - Tangential |
| Spark Free | No |
| Defrost setting | Auto (Off Cycle) |
| Controller Type | Digital BT, External |
| Battery Back Up/Hours | Yes/48hrs |
| Bluetooth | Yes |
| Number of Probes | 2 |
| Probe Type | Air & Load (Silicone Oil) |
| Ambient Temperature Range | 10°C to 32°C |
| Refrigerant Type | R600a/34g |
| UK 3 Pin Plug | Yes |
| Other Plug Types Available | No |
| Voltage Supply | 220-240V |
| Frequency (Hz) | 50Hz |
| Max Power (W) | 88W |
| Max Current Rating (A) | 0.65A |
| Energy Consumption (kWh/24h) | 1.04kWh/24h |
| Energy Consumption AE (kWh) | 379.6kWh |
| Noise Level (dB) | 39.9dB |
| Insulation Thickness (mm) | 45mm |
| Insulation Type | High Density Polyurethane Foam |
| Blowing Agent | Cyclopentane |
| Anti-Microbial Handle | Yes |