Pharmacy Plus Bluetooth Enabled Refrigerator

47L Pharmacy Plus Countertop Fridge with Solid Door

Product code PPSR47BT-UK

SKU code 444411305









Key features

- √ Temperature range of +2°C to +8°C
- √ Audible and visual temperature alarms
- √ Solid and glass door options
- ✓ Integrated lock, supplied with 2 keys for added security











Bluetooth Connected Controller

Our controller is Bluetooth enabled and allows for simple, contactless monitoring of temperature and alarm history, via the official Lec Medical app. Battery back-up, provides continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



SKU Code	444411305
Product Code	PPSR47BT-UK
Gross Capacity (litres)	47L
Net Capacity (litres)	35L
Unit External Width (mm)	475mm
Unit External Depth (mm)	445mm
Unit External Height (mm)	565mm
Product Weight (kg)	19.91kg
Packed Width (mm)	505mm
Packed Depth (mm)	510mm
Packed Height (mm)	585mm
Packed Weight (kg)	21.99kg UK
Country of Origin Internal Dimensions (mm) (WxDxH)	405mm x 355mm x 425mm
Temperature Range	+2°C to +8°C
Colour	White/Green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / HIPS*
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
Number of Door Trays	N/A
Number of Door Tray Positions	N/A
Door Open Depth (mm)	905mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock Adjustable Foot (number 8 position)	Yes, 2 Keys
Adjustable Feet (number & position) Porthole	2 Adjustable (front) Yes
Porthole Size	16mm
Porthole Location	Rear Bottom (Right)
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	1
Number of Shelf Positions	3
Shelf Size (mm) (WxDxH)	418mm x 200mm x 6mm
Shelf Size 2 (mm) (WxDxH)	N/A
Shelf Material	White Polythene Coated Wire
Drawer Size (mm) (WxDxH)	2@ 408mm x 405mm x 195mm
Drawer Size 2 (mm) (WxDxH)	
Drawer Material	N/A N/A
Drawer Material Number of Baskets	N/A 1
Number of Baskets	N/A 1
Number of Baskets Basket Material	
Number of Baskets Basket Material Basket Size (mm) (WxDxH)	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm
Number of Baskets Basket Material	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle)
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil)
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No 220-240V
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz)	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W)	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz)	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70 W
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A)	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70 W 0.6 A
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h)	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70 W 0.6 A 1.24 kWh/24h
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh)	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70 W 0.6 A 1.24 kWh/24h 452.3kWh
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Power (W) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Type	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70 W 0.6 A 1.24 kWh/24h 452.3kWh 46.7dB 35mm High Density Polyurothane Foam
Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth Number of Probes Probe Type Ambient Temperature Range Refrigerant Type UK 3 Pin Plug Other Plug Types Available Voltage Supply Frequency (Hz) Max Current Rating (A) Energy Consumption (kWh/24h) Energy Consumption AE (kWh) Noise Level (dB) Insulation Thickness (mm)	N/A 1 White Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / App Yes - Axial No Auto (Off Cycle) Digital BT, External Yes/48hrs Yes 2 Air & Load (Silicone Oil) 10°C to 32°C R600a/25g Yes No 220-240V 50/60Hz 70 W 0.6 A 1.24 kWh/24h 452.3kWh 46.7dB 35mm

