Laboratory Essential Freezer

39L Laboratory Essential Countertop Freezer with Solid Door

Product code LSFSF39DC-UK

SKU code 444411346







Key features

- √ Temperature range of -18°C to -25°C
- ✓ Air temperature probe

- \checkmark Audible and visual temperature alarms
- ✓ Factory fitted 16mm porthole for secondary temperature monitoring probes



External Digital Controller

Temperatures are easy to read on the clear digital display. Read, record, and reset simply with the touch of a button.



Fitted Lock

Integrated lock, comes with two keys for added security and access control, to keep contents safe.



Spark-free

We have removed items such as fans and lights so nothing in the interior of the appliance has a risk of igniting flammable liquids



Anti-Microbial Handle

Our handles have an anti-microbial powder coating which inhibits the growth of microbes to help prevent cross contamination.



SKU Code Product Code	444411346 LSFSF39DC-UK
Gross Capacity (litres)	39L
Net Capacity (litres)	35L
Unit External Width (mm)	475mm
Unit External Depth (mm)	445mm
Unit External Height (mm)	565mm
Product Weight (kg)	19kg
Packed Width (mm)	505mm
Packed Depth (mm)	510mm
Packed Height (mm)	585mm
Packed Weight (kg)	21.1kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	370mm x 345mm x 404mm
Temperature Range	-18°C to -25°C
Colour	White/Green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish Door Type	Painted Steel / Solid Solid
Door Type Door Style	Hinged, Reversible
Door Style Door Liner	Hinged, Reversible Flat
Number of Door Trays	N/A
Number of Door Tray Positions	N/A
Door Open Depth (mm)	905mm
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 Adjustable (front)
Porthole	Yes
Porthole Size	16mm
Porthole Location	Rear Bottom (Right)
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	
Number of Shelf Positions	7.CF man of V 10.0 man of V 10
Shelf Size (mm) (WxDxH) Shelf Material	365mm X 190mm X 10.8mm Polythene Coated Wire
Number of Baskets	Polytherie Coated Wife
Basket Material	Polythene Coated Wire
Basket Size (mm) (WxDxH)	363mm x 150mm x 152mm
Interior Light	No
Fan	No
Spark Free	Yes
Defrost setting	Manual
Controller Type	Digital, External
Number of Probes	1
Probe Type	Air
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a/40g
UK 3 Pin Plug	Yes
Other Plug Types Available	Yes
Voltage Supply	220-240V
Frequency (Hz)	50Hz
Max Power (W) Max Current Rating (A)	90W 0.8A
мах Current Rating (A) Energy Consumption (kWh/24h)	0.8A 1.40kWh/24hr
Energy Consumption (kWn/24n) Energy Consumption AE (kWh)	
Energy Consumption AE (kWn) Noise Level (dB)	511.0kWh 35.2dB
Insulation Thickness (mm)	53.2dB 50mm
· ,	
Insulation Type	High Density Polyurothane Foam
Blowing Agent Anti-Microbial Handle	Cyclopentane Yes

