Laboratory Plus Bluetooth Enabled Refrigerator

310L Laboratory Plus Upright Fridge with Solid Door

Product code LSFSR310BT-UK

SKU code 444411360







Key features

- √ Temperature range of +2°C to +10°C
- √ Air temperature probe

- ✓ Audible and visual temperature alarms
- √ Factory fitted 16mm porthole for secondary temperature monitoring probes











Bluetooth Connected Controller

Our upgraded controller is Bluetooth enabled and allows for simple, contactless monitoring of temperature and alarm history, via the official Lec Medical app.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via our bespoke smart phone app.
Downloadable temperature reports and alarm history.

Spark-free

We have removed items such as fans and lights so nothing in the interior of the appliance has a risk of igniting flammable liquids.

Anti-Microbial Handle

Our handles have an anti-microbial powder coating which inhibits the growth of microbes to help prevent cross contamination.

Flexible Internal Storage

Multiple shelf positions provide a flexible storage options for all your needs.



SKU Code	444411360
Product Code	LSFSR310BT-UK
Gross Capacity (litres)	310L
Net Capacity (litres)	310L
Unit External Width (mm)	595mm
Unit External Depth (mm)	600mm
Unit External Height (mm) Product Weight (kg)	1560mm 49.8kg
Product Weight (kg) Packed Width (mm)	49.0kg 640mm
Packed Width (mm)	635mm
Packed Height (mm)	1630mm
Packed Weight (kg)	55.3kg
Country of Origin	UK
nternal Dimensions (mm) (WxDxH)	500mm x 480mm x 1445mm
Temperature Range	+2°C to +10°C
Colour	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / HIPS*
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Balcony
Number of Door Trays Number of Door Tray Positions	<u>5</u>
Door Open Depth (mm)	1150mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 Adjustable (front)
Porthole	Yes
Porthole Size	16mm
Porthole Location	Rear Bottom (Right)
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms Number of Shelves/Drawers	Yes 5
Number of Shelf Positions	9
Shelf Size (mm) (WxDxH)	495mm x 325mm x 6mm
Shelf Size 2 (mm) (WxDxH)	487mm x 185mm x 6mm
Shelf Material	White Polythene Coated Wire
Drawer Size (mm) (WxDxH)	N/A
Drawer Size 2 (mm) (WxDxH)	N/A
Drawer Material	N/A
Number of Baskets	1
Basket Material	White Polythene Coated Wire
Basket Size (mm) (WxDxH)	485mm x 180mm x 171mm
nterior Light	No
Fan	No
Spark Free	Yes
Defrost setting Controller Type	Auto (Off Cycle) Digital BT, External
Bluetooth	Ves
Number of Probes]
Probe Type	Air
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a/34g
JK 3 Pin Plug	Yes
Other Plug Types Available	No
Voltage Supply	220-240V
Frequency (Hz)	50Hz
Max Power (W)	66W
Max Current Rating (A)	0.47A
Energy Consumption (kWh/24h)	0.69kWh/24h
Energy Consumption AE (kWh)	251.85kWh
Noise Level (dB)	39.9dB
nsulation Thickness (mm)	45mm
nsulation Type	High Density Polyurethane Foam
Blowing Agent Anti-Microbial Handle	Cyclopentane Yes

